

## Hard floor polish



**0,75L**

### PRODUCT DESCRIPTION

A waterborne environmental friendly protective refresher for varnished or lacquered wooden floors and parquet floors.

### TECHNNICAL DATA

SOLUTION	<b>water</b>
COLOUR	<b>clear</b>
PH	<b>8 - 9</b>
VOC	<b>2%, very low content of VOC</b>
DENSITY	<b>1,05 ± 0,05 kg/dm<sup>3</sup></b>

### USE

For all types of indoors varnished, sealed or lacquered floors. Prevents the floor of early abrasion.

New varnished or lacquered floor: wait 14 days before applying Hard floor Polish

### PREPARATION

Make the floor dust-free.

### APPLICATION

Pour some Hard floor polish on the floor. Spread it out with a clean, non-fluffing cloth or mop and finish it in strokes in the direction of the grain of the wood floor.

Clean floor completely, otherwise uneven sheen will occur.



### DRYING TIMES

1 hour at room temperature



### APPLYING QUANTITY

+/- 80 m<sup>2</sup>/ liter

### AFTER TREATMENT

For regular maintenance, use Hard floor fresh. When the general aspect of the floor starts to dull, apply a new coat of Hard floor polish.

After 5 to 10 coats it is better to remove the coats Hard floor polish with Hard floor cleaner and start over.

### PRODUCT INFORMATION

Storage: unopened in original packaging: 12 months. Store dry conditions between 5 and 25°C. Protect from frost.

### SPECIAL QUALITIES

Keep out of the reach of children. Do not mix with other cleaning products. If swallowed, seek medical advice immediately and show this container or label.

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

### Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare

Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be