

# Quality wax



5L 1L 0,5L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

### Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare  
Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

### PRODUCT DESCRIPTION

A traditional wax made with natural raw materials like African beeswax, candellilla wax, carnauba wax and pure turpentine oil.

### TECHNICAL DATA

APPEARANCE	<b>paste</b>
ODOUR	<b>turpentine</b>
DENSITY	<b>0,8</b>
SOLID CONTENT	<b>30%</b>

### USE

To wax furniture, beams, doors, marble or stone.

### PREPARATION

Sand the new wood with a 150 grit sandpaper and remove the sanding dust. You can use Aquacolor, reactive stain or Aquavintage Ciranova first to colour the wood.

### USER TIPS

Apply a thin coat with a paintbrush or cloth in the direction of the grain. Leave to dry for 12 hours and buff with a furniture brush or cloth.



### DRYING TIMES

12 hours at room temperature.



### APPLYING QUANTITY

7-12m<sup>2</sup>/l depending of the type of wood and preparation.

### AFTER TREATMENT

Use several layers of Ciranova Quality Wax. For maintenance, use Ciranova® Liquid Wax. Do not use varnish over wax polish.

### PRODUCT INFORMATION

Available colours : clear, yellow, brown, medium, antique, dark and mahogany. Storage : store in a well ventilated and cool place for up to 2 years.

### SPECIAL QUALITIES

This product is made from natural raw materials, including carnauba, candellilla, natural African beeswax and pure turpentine oil. Attention: Ciranova® Quality Wax is flammable.